



206 B. North Main St.
Jackson, CA 95642-2332

Telephone: (209) 223-5906
FAX: (209) 223-7994
Emergencies: (800) 255-3924
Outside U.S. &
Canada (Call Collect): (813) 248-0585

Section 1 – Product Identity as used on Label

FORTIFIED FLOOR WAX

MSDS Prepared: June 1999

Manufacturer: Franklin Cleaning Technology
P. O. Box 214
Great Bend, KS 67530

MATERIAL SAFETY DATA SHEET (MSDS)

Section 2 – Hazardous Ingredients/Identity Information

Hazardous Components <i>(Specific Chemical Identity/Common Names(s))</i>	CAS #	TWA	STEL	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Diethylene glycol monomethyl ether*	111-77-3	N/D	N/D	N/D	N/D	N/D	1

* Material subject to the reporting requirements of SARA Title III Section 313.

NFPA Ratings: Health: 1 Fire: 0 React: 0 Specific Hazard: N/D
HMIS Ratings: Health: 1 Fire: 0 React: 0 PPI: See Section 8

Section 3 – Physical/Chemical Characteristics

Boiling Point 212°F	Specific Gravity ($H_2O=1$) 1.0
Vapor Pressure (mm Hg) None	Melting Point None
Vapor Density (Air=1) >1	Freezing Point None
Solubility in Water Complete	Evaporation Rate (Butyl Acetate=1) N/D
Appearance and Odor Semi-translucent tan liquid, waxy polymeric odor	pH 9.1-9.7
	Percent Volatile Organics 84.6-85.2 by Volume

Section 4 – Fire and Explosion Hazard Data

Flash Point 1 (Method used) None; None	Flammable Limits (In air, % by volume)	LEL None	UEL None
Extinguishing Media Water, Foam, CO ₂	Auto Ignition Temperature N/D		
Special Fire Fighting Procedures None known.	Unusual Fire and Explosion Hazards N/D		

Section 5 – Reactivity Data

Stability:	Unstable	Stable XX	Conditions to avoid None known
Incompatibility (Materials to avoid) None known			
Hazardous Decomposition or Byproducts None known			
Hazardous Polymerization:	May Occur	Will Not Occur	Conditions to Avoid N/D

N/A = Not Applicable

N/D = No Data Available

N/E = Data Not Established

Continued on reverse

